



## GE Silicones

### MATERIAL SAFETY DATA SHEET

GEWP230 6PK-Pack (1.147 Lbs-0.521 Kg)

Trade Name Vinyl Spackling, White, Squeeze

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By **GESA Daytona Plant**  
703 South Street  
New Smyrna Beach FL 32168

Revised: 11/11/2003  
Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS  
Chemical Family/Use: Sealant  
Formula: Mixture  
CHEMTREC 1-800-424-9300

#### HMIS

FLAMMABILIT	0	REACTIVIT	0	HEALTH	1
Y		Y			

#### NFPA

FLAMMABILIT	0	REACTIVIT	0	HEALTH	1
Y		Y			

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION	CAS REG NO.	WGT. %
---------------------	-------------	--------

##### A. HAZARDOUS

Lead	7439-92-1	0.0001
1,4-Dioxane	123-91-1	0.0001
Formaldehyde	50-00-0	0.0001
Ethylene Oxide	75-21-8	0.0001
Cadmium	7440-43-9	0.0001
Arsenic	7440-38-2	0.0001
Acetaldehyde	75-07-0	0.0008

##### B. NON-HAZARDOUS

MAGNESIUM CARBONATE	7760-50-1	1 - 5 %
---------------------	-----------	---------



## ***GE Silicones***

### **MATERIAL SAFETY DATA SHEET**

**GEWP230 6PK-Pack (1.147 Lbs-0.521 Kg)**

**Trade Name                      Vinyl Spackling, White, Squeeze**

Kaolin	1332-58-7	1 - 5 %
VINYL ACETATE HOMOPOLYMER	9003-20-7	5 - 10 %
Water	7732-18-5	30 - 60 %
CALCIUM CARBONATE	471-34-1	30 - 60 %

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW:**

CAUTION! May cause skin, eye, and respiratory tract irritation.  
Solid White Unknown

#### **POTENTIAL HEALTH EFFECTS :**

##### **INGESTION :**

May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

##### **SKIN :**

May cause mild skin irritation.

##### **INHALATION :**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Can irritate mucous membranes and respiratory tract with coughing and shortness of breath. Avoid inhalation of vapour or mist.

##### **EYES :**

May cause mild eye irritation.

##### **MEDICAL CONDITIONS AGGRAVATED**

Pre-existing skin or respiratory diseases.

##### **SUBCHRONIC (TARGET ORGAN) :**

None known.



## ***GE Silicones***

### **MATERIAL SAFETY DATA SHEET**

**GEWP230 6PK-Pack (1.147 Lbs-0.521 Kg)**

**Trade Name**                      **Vinyl Spackling, White, Squeeze**

#### **CHRONIC EFFECTS / CARCINOGENICITY :**

This product or one of its ingredients present 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

#### **ROUTES OF EXPOSURE :**

dermal

#### **OTHER :**

None known.

### **4. FIRST AID MEASURES**

#### **INGESTION :**

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

#### **SKIN :**

Wash off with soap and water. Remove and wash contaminated clothing before re-use. Get medical attention if irritation or symptoms from Section 3 develop. Flush skin with large amounts of water for at least 15 minutes until no evidence of chemical remains.

#### **INHALATION :**

Seek medical attention if symptoms of exposure develop. Remove to fresh air.

#### **EYES :**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

#### **NOTE TO PHYSICIAN :**

Treatment is symptomatic and supportive.

### **5. FIRE-FIGHTING MEASURES**



**GEWP230 6PK-Pack (1.147 Lbs-0.521 Kg)**

<b>Trade Name</b>	<b>Vinyl Spackling, White, Squeeze</b>
-------------------	--

## Unknown

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

Wear suitable protective equipment. Collect spilled material and place in closed container for recovery or disposal.

Avoid contact with skin and eyes. Remove and wash contaminated clothing before re-use. Keep away from children. Keep container dry. Store away from heat, sources of ignition, and incompatibles. Avoid accidental ingestion of this material. Wash hands and face before eating, drinking, smoking, using toilet facilities, or applying cosmetics. Avoid inhalation of vapour or mist.



## **GE Silicones**

### **MATERIAL SAFETY DATA SHEET**

**GEWP230 6PK-Pack (1.147 Lbs-0.521 Kg)**

**Trade Name**                      **Vinyl Spackling, White, Squeeze**

#### **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

##### **ENGINEERING CONTROLS :**

Eyewash stations

##### **RESPIRATORY PROTECTION:**

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

##### **PROTECTIVE GLOVES :**

impervious gloves

##### **EYE AND FACE PROTECTION :**

safety glasses with side-shields

##### **OTHER PROTECTIVE EQUIPMENT :**

Wear suitable protective clothing and eye/face protection.

##### **Exposure Guidelines**

**Chemical**

**CAS REG NO.**

**ACGIH**

**OSHA**

**Supplier**

#### **9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>BOILING POINT - C &amp; F</b>	Unknown
<b>VAPOR PRESSURE (20 C) (MM HG) :</b>	Unknown
<b>VAPOR DENSITY (AIR=1) :</b>	
<b>FREEZING POINT:</b>	Unknown
<b>MELTING POINT :</b>	Unknown
<b>PHYSICAL STATE:</b>	Solid
<b>ODOR:</b>	Unknown
<b>COLOR :</b>	White



## ***GE Silicones***

### **MATERIAL SAFETY DATA SHEET**

**GEWP230 6PK-Pack (1.147 Lbs-0.521 Kg)**

**Trade Name**                      **Vinyl Spackling, White, Squeeze**

#### **EVAPORATION RATE (BUTYL**

**ACETATE=1):**

**SPECIFIC GRAVITY (WATER=1) :**                      15.45

**DENSITY (KG/M3) :**                                      Unknown

**ACID / ALKALINITY (MEQ/G) :**                      Unknown

**pH**    Unknown

#### **VOLATILE ORGANIC CONTENT (VOL)**

**SOLUBILITY IN WATER (20 C) :**                      Insoluble

**SOLUBILITY IN ORGANIC SOLVENT**                      Unknown

**(STATE SOLVENT) :**

**VOC EXCL. H2O & EXEMPTS (G/L) :**                      0.24

### **10. STABILITY AND REACTIVITY**

**STABILITY :**

Stable

**HAZARDOUS POLYMERIZATION :**

WILL NOT OCCUR

**HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS :**

Unknown

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Unknown

**CONDITIONS TO AVOID :**

Unknown

### **11. TOXICOLOGICAL INFORMATION**

**ACUTE ORAL:**

Unknown



## ***GE Silicones***

### **MATERIAL SAFETY DATA SHEET**

**GEWP230 6PK-Pack (1.147 Lbs-0.521 Kg)**

**Trade Name**                      **Vinyl Spackling, White, Squeeze**

**ACUTE DERMAL:**

Unknown

**ACUTE INHALATION:**

Unknown

**OTHER:**

None

**SENSITIZATION:**

**SKIN IRRITATION**

**EYE IRRITATION**

**MUTAGENICITY**

Unknown

## **12. ECOLOGICAL INFORMATION**

**ECOTOXICOLOGY**

no data available

**CHEMICAL FATE**

no data available

**DISTRIBUTION**

## **13. DISPOSAL CONSIDERATIONS**



## ***GE Silicones***

### **MATERIAL SAFETY DATA SHEET**

**GEWP230 6PK-Pack (1.147 Lbs-0.521 Kg)**

**Trade Name**                      **Vinyl Spackling, White, Squeeze**

#### **DISPOSAL METHOD :**

Disposal should be made in accordance with federal, state and local regulations.

#### **14. TRANSPORT INFORMATION**

**Not Regulated if Section is Blank**

#### **15. REGULATORY INFORMATION**

##### **US Regulatory Information**

##### **CERCLA**

**PRODUCT COMPOSITION**    **Chemical**

**CERCLA Reportable  
Quantity**

**CLEAN AIR ACT**

**CLEAN WATER ACT**

**SARA SECTION 302 :**

**SARA (311,312) HAZARD CLASS:**

Acute Health Hazard

**SARA (313) CHEMICALS :**

##### **Canadian Regulatory Information**





## ***GE Silicones***

### **MATERIAL SAFETY DATA SHEET**

**GEWP230 6PK-Pack (1.147 Lbs-0.521 Kg)**

**Trade Name**                      **Vinyl Spackling, White, Squeeze**

**WHMIS HAZARD CLASS :**  
D2B TOXIC MATERIALS

**OTHER:**

**SCHDLE B/HTSUS:**

**ECCN:**

**CALIFORNIA PROPOSITION 65 :**

Warning! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm

7439-92-1,Lead

123-91-1,1,4-Dioxane

50-00-0,FORMALDEHYDE

75-21-8,ETHYLENE OXIDE

7440-43-9,Cadmium

7440-38-2,Arsenic

75-07-0,

### **16. OTHER INFORMATION**

**OTHER :**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate....., C = ceiling limit      NEGL = negligible  
EST= estimated      NF = none found      NA = not applicable  
UNKN = unknown      NE = none established      REC = recommended      ND = none determined  
V = recomm. By vendor      By-product = reaction by      SKN = skin product, TSCA inventory      TS = trade secret status not required under      R =



***GE Silicones***

**MATERIAL SAFETY DATA SHEET**

**GEWP230 6PK-Pack (1.147 Lbs-0.521 Kg)**

**Trade Name                      Vinyl Spackling, White, Squeeze**

recommended 40 CFR part 720.30(h-2)    MST = mist STEL = short term exposure  
NT = not tested    limit.....